

## Wall mounted unit

FTXC-C / RXC-C

BLUEEVOLUTION sensira



Energy saving during standby mode



Daikin Residential Controller app

Wall mounted unit, offering good value for money

- › Flat, stylish front panel blends easily with any interior décor and is easier to clean
- › Online controller (optional)

- › Seasonal efficiency values up to A++ in cooling
- › Bluevolution range: lower environmental impact

# FTXC-C / RXC-C



FTXC-C




RXC20-35C

Efficiency data		FTXC + RXC	20C + 20C	25C + 25C	35C + 35C	50C + 50C	60C + 60C	71C + 71C	
Cooling capacity	Min./Max.	kW	1.3 /3.0		1.3 /4.0	1.4 /6.2	1.8 /7.0	2.3 /7.3	
Heating capacity	Min./Max.	kW	1.30 /4.00		1.30 /4.80	1.36 /6.60	1.48 /8.00	2.30 /9.00	
Space cooling	Energy efficiency class		A++						
	Capacity	Pdesign	kW	2.08	2.57	3.44	5.08	6.21	6.96
	SEER			6.89	6.84	6.87	6.45	6.40	5.30
	η <sub>s,c</sub>		%	-					
	Annual energy consumption	kWh/a	106	132	175	276	340	459	
Space heating (Average climate)	Energy efficiency class		A+						
	Capacity	Pdesign	kW	1.87	2.23	2.24	3.90	4.10	6.35
	SCOP/A			4.40	4.45	4.28	4.42	4.24	3.81
	η <sub>s,h</sub>		%	-					
		Annual energy consumption	kWh/a	594	700	732	1,236	1,354	2,334

Indoor unit		FTXC	20C	25C	35C	50C	60C	71C			
Dimensions	Unit	HeightxWidthxDepth	288 x770 x234				297 x990 x273				
Weight	Unit		9.00		9.50		13.0				
Air filter	Type		Removable / washable								
Fan	Air flow rate	Cooling	5.4 /6.5 /9 /10.8			7.4 /8.2 /10 /12.2		10.2 /13.6 /16 /20.4			
Sound power level	Cooling		54		55		57		60		
Sound pressure level	Cooling	Silent operation/Low/High	20 /26 /38		21 /26 /39		29 /33 /45		30 /38 /46		
Control systems	Infrared remote control		ARC486A2								
	Wired remote control		-								

Outdoor unit		RXC	20C	25C	35C	50C	60C	71C		
Dimensions	Unit	HeightxWidthxDepth	550 x658 x273			615 x845 x300		695 x930 x350		
Weight	Unit		24.0		26.0		39.0		45.0	
Sound power level	Cooling		58		60		65		66	
Sound pressure level	Cooling	High	45		46		51		54	
Operation range	Cooling	Ambient	Min.~Max.		10 ~46		-10 ~46			
	Heating	Ambient	Min.~Max.		-15 ~18					
Refrigerant	Type		R-32							
	GWP		675.0							
	Charge		0.550 /0.371		0.750 /0.506		1.00 /0.675		1.10 /0.743	
Piping connections	Liquid	OD	6.4							
	Gas	OD	9.52			12.7				
	Piping length	OU - IU	Max.		20		30			
	System	Chargeless	8							
	Additional refrigerant charge		0,017 (for piping length exceeding 7.5m)							
	Level	IU - OU	Max.		15.0		20.0			
Power supply	Phase/Frequency/Voltage		1~/50 /220-240							
Current - 50Hz	Maximum fuse amps (MFA)		A							

Daikin Europe N.V. Naamloze Vennootschap · Zandvoordestraat 300 · 8400 Oostende · Belgium · www.daikin.eu · BE 0412 120 336 · BE 0412 120 336 (Responsible Editor)



Daikin Europe N.V. participates in the Eurovent Certified Performance programme for Fan Coil Units and Variable Refrigerant Flow systems. Check ongoing validity of certificate: [www.eurovent-certification.com](http://www.eurovent-certification.com)

ECPEN21-045

12/2020



The present publication is drawn up by way of information only and does not constitute an offer binding upon Daikin Europe N.V. / Daikin Central Europe HandelsGmbH. Daikin Europe N.V. / Daikin Central Europe HandelsGmbH have compiled the content of this publication to the best of their knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin Europe N.V. / Daikin Central Europe HandelsGmbH explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this publication. All content is copyrighted by Daikin Europe N.V.