

# Technical specifications



Casing	Colour		W = White (RAL 9003 (glossy)) S = Silver (RAL 9006 (metallic)) K = Black (RAL 9005 (matt))
	LED operation	Colour	Blue status indicator
Dimensions	Unit	Height x Width x Depth	mm
Weight	Unit		kg
LCD	Back light	Colour	White
Maximum number of connectable indoor units			1 group (up to 16 indoor units)
Wiring connections	For connection with indoor		P1-P2 wired connection from indoor unit
	Size		mm <sup>2</sup>
Ambient temperature	Operation		Min.~Max.
	Relative humidity		
	Storage		Min.~Max.
Back-up for power failure			Yes - clock stays synchronised for up to 48 hours.
Bluetooth® wireless technology	Protocol		Bluetooth® low energy 4.2 or higher
App for advanced settings			Madoka Assistant
App operation system			Apple iOS 8.0 or higher, Android 5.0 or higher

## Daikin Europe N.V.

Naamloze Vennootschap Zandvoordestraat 300 · 8400 Ostend · Belgium  
www.daikin.eu · BE 0412 120 336 · RPR Oostende (Responsible Editor)

The present publication is drawn up by way of information only and does not constitute an offer binding upon Daikin Europe NV. Daikin Europe N.V. has compiled the content of this publication to the best of its knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin Europe N.V. explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this publication. All content is copyrighted by Daikin Europe N.V.

Printed on non-chlorinated paper.

Prepared by La Movida, Belgium.

ECPEN18-306

0000 - 06/18

