

Specifications Table for FDXM-F9

				FDXM25F3V1 B9	FDXM35F3V1B9	FDXM50F3V1B9	FDXM60F3V1 B9	
Power input	Cooling	Nom.	kW	0.036	0.036	0.060	0.060	
Dimensions	Unit	Height	mm	200	200	200	200	
		Width	mm	750	750	1,150	1,150	
		Depth	mm	620	620	620	620	
Weight	Unit		kg	21	21	28	28	
Fan	Air flow rate	Cooling	High	m³/min	8.7	8.7	15.8	16.0
			Medium	m³/min	8.0	8.0	14.6	14.8
			Low	m³/min	7.3	7.3	13.3	13.5
	Heating	High	m³/min	8.7	8.7	15.8	16.0	
		Medium	m³/min	8.0	8.0	14.6	14.8	
		Low	m³/min	7.3	7.3	13.3	13.5	
	External static pressure	Nom.	Pa	30	30	40	40	
Sound power level	Cooling		dBA	53.0	53.0	55.0	56.0	
	Heating		dBA	53.0	53.0	55.0	56.0	
Sound pressure level	Cooling	High	dBA	35.0	35.0	38.0	38.0	
		Medium	dBA	33.0	33.0	35.0	35.0	
		Low	dBA	27.0	27.0	30.0	30.0	
	Heating	High	dBA	35.0	35.0	38.0	38.0	
		Medium	dBA	33.0	33.0	35.0	35.0	
		Low	dBA	27.0	27.0	30.0	30.0	
Piping connections	Liquid	OD	mm	6.35	6.35	6.35	6.35	
	Gas	OD	mm	9.50	9.50	12.70	12.70	
	Drain			VP20 (I.D. 20/O.D. 26)	VP20 (I.D. 20/O.D. 26)	VP20 (I.D. 20/O.D. 26)	VP20 (I.D. 20/O.D. 26)	
Standard Accessories	Installation manual			1	1	1	1	
	Operation manual			1	1	1	1	
	Insulation for fitting			1	1	1	1	
	Sealing pad			1	1	1	1	
	Clamp metal			1	1	1	1	
	Drain hose			1	1	1	1	
	Washer for hanger bracket			8	8	8	8	
	Sealing material			2	2	2	2	
	Clamps			6	6	6	6	
	Washer fixing plate			4	4	4	4	
	Screws for duct flanges			1	1	1	1	
Air filter			1	1	1	1		
Power supply	Phase			1~	1~	1~	1~	
	Frequency	Hz	50	50	50	50		
	Voltage	V	220-240	220-240	220-240	220-240		
Notes				(1) - See separate drawing for electrical data	(1) - See separate drawing for electrical data	(1) - See separate drawing for electrical data	(1) - See separate drawing for electrical data	