

Specifications Table for 2MXM-M9

					2MXM50M3V1B9	2MXM50M2V1B9 (Archived)
Dimensions	Unit	Height	mm	550	550	
			Width	mm	765	765
			Depth	mm	285	285
Weight	Unit		kg	41	41	
Fan motor	Speed	Cooling	Super low	rpm	500	500
		Heating	Super low	rpm	500	500
Compressor	Type				Hermetically sealed swing compressor	Hermetically sealed swing compressor
Sound pressure level	Cooling	High	dB(A)	48	48	
	Heating	High	dB(A)	50	50	
Refrigerant	Type				R-32	R-32
	Charge	kg			1.15	1.15
	Charge	TCO2Eq			0.78	0.8
	GWP				675	675.0
Piping connections	Additional refrigerant charge			kg/m	0.02 (for piping length exceeding 20m)	0.02 (for piping length exceeding 20m)
	Level difference	IU - OU	Max.	m	15.0	15.0
		IU - IU	Max.	m	7.5	7.5
	Total piping length	System	Actual	m	30.0	30.0
Standard Accessories	Installation manual				1	1
	Screw bag				1	1
	Drain plug				1	1
	Reducer assembly				1	1
Power supply	Phase				1~	1~
	Frequency			Hz	50	50
	voltage			V	220-230-240	220-230-240
Notes					(1) - For one room	(1) - Every D-AHU Professional can be designed to your needs. Select your AHU on tools.daikinapplied.eu
					(2) - See separate drawing for operation range	(2) - See separate drawing for operation range
					(3) - See separate drawing for electrical data	(3) - See separate drawing for electrical data
					(4) - Contains fluorinated greenhouse gases	(4) - Contains fluorinated greenhouse gases