

## Specifications Table for 3MXM-N

				3MXM40N2V1B	3MXM52N2V1B	3MXM68N2V1B	
Dimensions	Unit	Height	mm	734	734	734	
		Width	mm	958	958	958	
		Depth	mm	340	340	340	
Weight	Unit		kg	57	57	62	
Fan	Air flow rate	Cooling	Super low	cfm	847	847	851
			Super low	m <sup>3</sup> /min	24	24	24.1
	Heating	Super low	cfm	847	847	851	
		Super low	m <sup>3</sup> /min	24	24	24.1	
Fan motor	Speed	Cooling	Super low	rpm	420	420	
		Heating	Super low	rpm	420	420	
Compressor	Type			Hermetically sealed swing compressor	Hermetically sealed swing compressor	Hermetically sealed swing compressor	
Operation range	Cooling	Ambient	Min.	°CDB	-10	-10	-10
			Max.	°CDB	46	46	46
	Heating	Ambient	Min.	°CWB	-15	-15	-15
			Max.	°CWB	18	18	18
Sound pressure level	Cooling		Nom.	dB(A)	46	46	48
	Heating		Nom.	dB(A)	47	47	48
Refrigerant	Type			R-32	R-32	R-32	
	Charge		kg	1.80	1.80	2.00	
	Charge		TCO <sub>2</sub> Eq	1.2	1.2	1.4	
	GWP			675	675	675	
Piping connections	Additional refrigerant charge			kg/m	0.02 (for piping length exceeding 30m)	0.02 (for piping length exceeding 30m)	0.02 (for piping length exceeding 30m)
	Level difference	IU - OU	Max.	m	15	15	15
		IU - IU	Max.	m	7.5	7.5	7.5
Total piping length	System	Actual	m	50	50	50	
Standard Accessories	Installation manual				1	1	1
	Screw bag				1	1	1
	Drain plug				1	1	1
Power supply	Phase				1~	1~	1~
	Frequency			Hz	50	50	50
	Voltage			V	220-240	220-240	220-240
Notes					(1) - Contains fluorinated greenhouse gases	(1) - Contains fluorinated greenhouse gases	(1) - Contains fluorinated greenhouse gases
Standard Accessories	Drain cap (1)						6
	Drain cap (2)						3
	Reducer assembly						1