

Specifications Table for 4MXM-N

					4MXM68N2V1B (Archived)	4MXM80N2V1B (Archived)
Dimensions	Unit	Height	mm		734	734
			Width	mm	958	958
			Depth	mm	340	340
Weight	Unit			kg	63	67
Fan	Air flow rate	Cooling	Super low	cfm	851	851.0
			Super low	m ³ /min	24.1	24.1
		Heating	Super low	cfm	851.0	851.0
			Super low	m ³ /min	24.1	24.1
Compressor	Type				Hermetically sealed swing compressor	Hermetically sealed swing compressor
Operation range	Cooling	Ambient	Min.	°CDB	-10	-10
			Max.	°CDB	46	46
	Heating	Ambient	Min.	°CWB	-15	-15
			Max.	°CWB	18	18
Sound pressure level	Cooling		Nom.	dBA	48	49
	Heating		Nom.	dBA	48	49
Refrigerant	Type				R-32	R-32
	Charge			kg	2.00	2.40
	Charge			TCO2Eq	1.4	1.6
	GWP				675	675
Piping connections	Additional refrigerant charge			kg/m	0.02 (for piping length exceeding 30m)	0.02 (for piping length exceeding 30m)
	Level difference	IU - OU	Max.	m	15	15
		IU - IU	Max.	m	7.5	7.5
	Total piping length	System	Actual	m	60	70
Standard Accessories	Installation manual				1	1
	Screw bag				1	1
	Drain plug				1	1
	Drain cap (1)				6	6
	Drain cap (2)				3	3
	Reducer assembly				1	1
Power supply	Phase				1~	1~
	Frequency			Hz	50	50
	Voltage			V	220-240	220-240
Notes					(1) - Contains fluorinated greenhouse gases	(1) - Contains fluorinated greenhouse gases