

Streamer technology air purifier

MC30YV



Flash Streamer

Powerful air purification

- › Pure air thanks to Daikin 'Catch and Clean' approach in decomposing harmful substances
- › High performance electrostatic HEPA filter which doesn't clog easily, hence causes low pressure loss
- › One of the most silent Air Purifier range on the European market
- › No need to change the filter for ten years, resulting in low maintenance costs
- › Purifies the air in rooms up to 46m²

MC30YV



MC30YV

Indoor Unit		MC	30YVM
Application			Floor standing type
Applicable room area		m ²	23 (1) / 46 (2)
CADR		m ³ /h	180 (3)
Weight	Unit	kg	5.8
Dimensions	(H x W x D)	mm	450 / 270 / 270
Casing	Colour		White
Fan	Type		Multi Blade Fan (Sirocco fan)
	Air flow rate	Air purifying operation Silent/Medium/Turbo	m ³ /h 60 /120 /180
Sound pressure level (4)	Air purifying operation	Silent/Medium/Turbo	dBA 19 /27 /37
Air purifying operation	Power input	Silent/M/Turbo	kW 0.008 /0.015 /0.025
Deodorizing method			Flash streamer + Deodorizing catalyst
Dust collecting method			Electrostatic HEPA filter (5)
Air filter	Type		Polyethylene terephthalate net
Sign	Item	01	Child proof lock lamp / ON/OFF lamp / Streamer lamp / Sleep mode
Power supply	Phase/Frequency/Voltage	Hz/V	1~/50/60/220-240/220-230
Type			Air Purifier

(1) The applicable room area is appropriate for operating the unit of maximum fan speed (HH). Applicable room area indicates the space where a certain amount of dust particles can be removed in 30 minutes. (JEM 1467) |

(2) The applicable room area is appropriate for operating the unit of maximum fan speed (HH). Applicable room area was calculated in accordance with NRCC-5401 standard using cigarette smoke CADR that was tested according to JEM 1467. |


(3) Converted to CADR standards from test values in accordance with JEM 1467. |

(4) Operating sound levels are the average of values measured at 1m away from the front, left, right and top of the unit. (These are equal to the values in an anechoic chamber) |

(5) Electrostatic HEPA filter is attached in the unit. |

(6) Other function : Auto-restart function.

Daikin Europe Naamloze Vennootschap · Zandvoordestraat 300 · 8400 Oostende · Belgium · <https://www.daikin.eu> · RPR Oostende (Responsible Editor)



ECPEN22-612A

06/2022

The present publication is drawn up by way of information only and does not constitute an offer binding upon Daikin Europe N.V. / Daikin Central Europe HandelsGmbH. Daikin Europe N.V. / Daikin Central Europe HandelsGmbH have compiled the content of this publication to the best of their knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin Europe N.V. / Daikin Central Europe HandelsGmbH explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this publication. All content is copyrighted by Daikin Europe N.V.

